

## “SEA LION” SPECIFICATIONS

<b>TYPE:</b>	Wave Piercer	<b>DISPL:</b>	17,764 Heavy 10,800 Light
<b>LOA:</b>	45'	<b>DRAFT:</b>	1'6"
<b>LWL:</b>	45'	<b>DESIGNER:</b>	Gold Coast Yachts
<b>ENGINES:</b>	2 X 200 Hp Yamaha Outboards <b>FUEL:</b> 16 gal.		
<b>CRUISE SPEED:</b>	22 knots	<b>MAX SPEED:</b>	25 knots
<b>PASSENGERS:</b>	22 divers (double tank) <b>BUILDER:</b> Gold Coast Yachts		

**CONSTRUCTION DETAILS:** Fir strip planked hull bottoms glassed inside with unidirectional E glass and stringer frame plywood topsides, exterior of hull glassed with triaxial glass Stringer/frame/plywood/fiberglassed cabin structure, beams, bridgedeck, extended roof and partitions. All materials marine grade, laminated, coated and glassed with WEST SYSTEM epoxy resin. Miscellaneous teak trim on bulkheads, roof and bar.

**LAYOUT:** Captain's seat, central aluminum framed bench seating with C-Cushions; side wall seating with dive tank storage; storage compartment, head with sink and toilet. Aft deck seat storage lockers. Rubber padded protected floor. 10' Custom dive platform with handrails and below water T ladders. Fixed plexiglass windshield. Roll up vinyl side windows.

**FINISH:** Exterior Awlgrip Polyurethane paint over epoxy primer – commercial yacht finish.

**PAINT & GRAPHICS:** Matterhorn White topsides and Aristo Blue window stripe, Black bottom paint.

**TANKAGE:** 168 gallons fuel, 33 gallons water

**ENGINE:** 2 –200 HP BETOUL Yamaha counter rotating outboards. Dual binnacle mount, tachometers, engine alarms, powertilt/trim. Teleflex hydraulic steering.

**PLUMBING, PUMPS & FITTINGS:** All emergency piping is rigid PVC. Water supply hosing is rigid PVC and reinforced vinyl hose. 1 Henderson MKV emergency bilge pump. 1 Par Pressure pump with spigot and hose. 1 Raritan PHII hand toilet with Marelon thruhull and seacock.

### ELECTRONICS:

- 1 Cassette Stereo with 2 speakers
- 1 Standard Horizon Eclipse VHF
- 1 3" Danforth highspeed compass
- 1 Marinetics 12 Volt electrical panel with voltmeter
- 1 Battery selector switch
- 2 90 amp. Starting batteries
- 1 Port and starboard bowlight, sternlight and anchor/steaming light
- 1 Interior fluorescent light fixture (head)
- 2 Dome lights
- 1 12v outlet
- 1 windshield wiper

---

**SAFETY EQUIPEMENT:**

2 ABC 10 lb. fire extinguishers

**GROUND TACKLE:**

1 22S Danforth, 15' 5/16" chain and 150' of 5/8" rode  
1 20 lb. D2000 Danforth, 15' 5/16" chain and 150' of 5/8" rode  
4 50 ½" dock lines  
4 Scanmarin fenders F4  
1 Full length rigid vinyl rubrail

**DECK GEAR:**

4 12" SS cleats  
2 10" SS cleats  
6 24" SS handrails  
2 Tempress small utility hatches  
2 Lewmar Size 50 Ocean Hatches (hull access)  
1 Lewmar Size 50 Trimline Hatch (Captain's ventilation)

Considered US built. Can be USCG certified for 30 passengers in a shuttle/ferry arrangement.